

3 POLE POWER MINI-CONTACTORS

Motor Duty AC3/415V 50 Hz		AC1 Duty (Amp)	Standard Aux. Contacts		Cat No.*	LP (Rs.)	Standard AC coil Voltage 50 Hz	Non-Standard** AC Coil Voltage 50 Hz Available Range
Current (Amp)	kW		No	NC				

MINI-CONTACTORS CA4 FROM 5 AMP TO 12 AMP WITH AC COIL

5.3A	2.6	20A	1	-	CA4-5-10...V50	495	24, 48, 110, 220-230, 380-400V	12...500V Add on price Rs.30/-
5.3A	2.6	20A	-	1	CA4-5-01...V50	495		
9A	4.5	20A	1	-	CA4-9-10...V50	520		
9A	4.5	20A	-	1	CA4-9-01...V50	520		
12A	5.5	20A	1	-	CA4-12-10...V50	590		
12A	5.5	20A	-	1	CA4-12-01...V50	590		

MINI-CONTACTORS CA4 FROM 5 AMP TO 12 AMP WITH DC COIL

5.3A	2.6	20A	1	-	CA4-5C-10...VDC	710	24, 48, 110, 220V	12...500V Add on price Rs.30/-
5.3A	2.6	20A	-	1	CA4-5C-01...VDC	710		
9A	4.5	20A	1	-	CA4-9C-10...VDC	730		
9A	4.5	20A	-	1	CA4-9C-01...VDC	730		
12A	5.5	20A	1	-	CA4-12C-10...VDC	800		
12A	5.5	20A	-	1	CA4-12C-01...VDC	800		

MINI CONTROL RELAYS

AC1 Duty (Amp)	AC15 400V AC (Amp)	AC3 at 400V 50 kW	Standard Aux. Contacts		Cat No.*	LP (Rs.)	Standard AC coil Voltage	Non-Standard** AC Coil Voltage Available Range
			No	NC				

CS4 MINI-CONTROL RELAYS WITH AC COIL

16A	2.5A	1.7	4	-	CS4-40E...V50	515	24, 48,110, 220-230, 380-400, 440V 50Hz	12..500V 50Hz Add on price Rs.30/-
			3	1	CS4-31Z...V50	515		
			2	2	CS4-22Z...V50	515		

CS4 MINI-CONTROL RELAYS WITH DC COIL

16A	2.5A	1.7	4	-	CS4C-40E...VDC	740	24, 48, 110, 125, 220V DC	12..250V VDC Add on price Rs.30/-
			3	1	CS4C-31Z...VDC	740		
			2	2	CS4C-22Z...VDC	740		

* The above Cat. No. is incomplete. To complete the cat. no., select a coil voltage from the table and insert into the cat. no. For example Mini Control Relay with 4 N.O. & with 220V 50Hz coil will be selected as the cat. no. CS4-40E-220V 50

** Contactor with Non-standard coil voltages are available at an extra cost as shown in non-standard coil voltage column and minimum order quantity of 10 pcs.