

强制性认证产品符合性自我声明

自我声明编号: 2020970305001007



Rockwell Automation, Inc. (生产者) 及 罗克韦尔自动化(中国)有限公司(生产者授权代表) 确知知晓《强制性产品认证自我声明实施规则》以及相关产品强制性认证实施规则的要求, 对本声明承担全部法律责任。

Rockwell Automation, Inc. (生产者) 及 罗克韦尔自动化(中国)有限公司(生产者授权代表) 声明以下产品已按照《强制性产品认证自我声明实施规则》以及相关产品强制性认证实施规则的要求进行检测, 符合相关标准要求; 自本声明签署之日起, 生产和销售的产品持续符合以下标准与实施规则的要求; 保存本声明涉及的技术文档至少10年; 正确使用强制性产品认证标志; 如产品或其符合性信息发生变更, 将及时更新技术文档并报送产品变更信息。

生产者名称: Rockwell Automation, Inc.
生产者地址: 1201 South Second Street, Milwaukee WI 53204, USA
依据的强制性产品认证规则: CNCA-C03-02:2014 低压元器件
产品名称: 按钮开关及指示灯
产品系列、型号、规格: (见附页)
依据的标准: GB/T14048.5-2017
生产企业名称: 罗克韦尔自动化控制集成(上海)有限公司
生产企业地址: 上海市浦东新区创业路565号, T20-2通用厂房

生产者联系信息

名称: Rockwell Automation, Inc.
地址: 1201 South Second Street, Milwaukee WI 53204, USA
联系人: 钱汝程
电话: 021-61288888
电子邮箱: lilpan@ra.rockwell.com
自我声明时间: 2020-05-12
自我声明地点: 上海
指定签字人: 
签章: 

授权代表信息

名称: 罗克韦尔自动化(中国)有限公司
地址: 上海市市辖区徐汇区虹梅路1801号宏业大厦
联系人: 潘亮
电话: 021-61288888
电子邮箱: lilpan@ra.rockwell.com
自我声明时间: 2020-05-12
自我声明地点: 上海
指定签字人: 
签章: 

注: 有关本声明信息真伪可登录全国认证认可信息公共服务平台 (cx.cnca.cn) 或扫描右上角二维码查询。

强制性认证产品符合性自我声明(附页)



自我声明编号: 2020970305001007

产品系列、型号、规格:

800FD...D7D...; Ui:300V; Uimp:2.5kV; Ith:5A; AC-15:Ue/Ie:120V/3A, 240V/1.5A; DC-13:Ue/Ie:125V/0.22A, 250V/0.1A; 指示灯:Ue:AC/DC48V, 120V, 240V; 安装孔径: Φ22.5mm; 防护等级: IP20, IP66(工作面). 型号解释详见附件

生产者联系信息

名称: Rockwell Automation, Inc.
地址: 1201 South Second Street, Milwaukee WI 53204, USA
联系人: 钱汝程
电话: 021-61288888
电子邮箱: lilpan@ra.rockwell.com
自我声明时间: 2020-05-12
自我声明地点: 上海
指定签字人: 
签章: 

授权代表信息

名称: 罗克韦尔自动化(中国)有限公司
地址: 上海市市辖区徐汇区虹梅路1801号宏业大厦
联系人: 潘亮
电话: 021-61288888
电子邮箱: lilpan@ra.rockwell.com
自我声明时间: 2020-05-12
自我声明地点: 上海
指定签字人: 
签章: 

注: 有关本声明信息真伪可登录全国认证认可信息公共服务平台 (cx.cnca.cn) 或扫描右上角二维码查询。

附录：

自我声明编号：2020970305001007



1. 型号的解释（如适用）：

800FD	-	F	I	X	0	I	-	BP
I		II	III	IV	V	VI		VII

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type E – Push button, non-illuminated, momentary, extended F – Push button, non-illuminated, momentary, flush
III.	Assortment of colors Any number 0 through 9 – Operator cap color and legend
IV.	Type of Wire Termination X – For Stripped Wire R – For Ring Lug
V.	Number of N.O. Contacts 0, 1 or 2
VI.	Number of N.C. Contacts 0, 1 or 2
VII.	Packing Options (With –BP means products are shipped in bulk packing) Letters may be used to denote packaging options



注：此附录与自我声明同时使用时有效。

附录:

第 2 页 共 4 页

自我声明编号: 2020970305001007

800FD Emergency Stop Operator Modules:

800FD	-	MT	4	4	X	2	0	-	BP
I		II	III	IV	V	VI	VII		VIII

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type MT – Mushroom button, non-illuminated, push-pull/twist-to-release
III.	Mushroom Button Size 3 – 30 mm 4 – 40 mm 6 – 60 mm
IV.	Assortment of colors Any number 0 through 9 is used to denote operator color and legend
V.	Type of Wire Termination X – For Stripped Wire R – For Ring Lug
VI.	Number of N.O. Contacts 0, 1 or 2
VII.	Number of N.C. Contacts 0, 1 or 2
VIII.	Packing Options Letters may be used to denote packaging options

注: 此附录与自我声明同时使用时有效。

附录:

第 3 页 共 4 页

自我声明编号: 2020970305001007

800FD	-	S	B	3	2	X	1	1	-	BP
I		II	III	IV	V	VI	VII	VIII		IX

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type S – Selector switch, non-illuminated, standard knob
III.	Operator Function B – Spring return from left and right L – Spring return from left M – Maintained R – Spring return from right
IV.	Switch Positions 2 – Two positions 3 – Three positions
V.	Assortment of colors Any number 0 through 9 is used to denote operator color and legend
VI.	Type of Wire Termination X – For Stripped Wire R – For Ring Lug
VII.	Number of N.O. Contacts 0, 1 or 2
VIII.	Number of N.C. Contacts 0, 1 or 2
IX.	Packing Options Letters may be used to denote packaging options

注: 此附录与自我声明同时使用时有效。

附录:

第 4 页 共 4 页

自我声明编号: 2020970305001007

800FD Pilot Light Operator Modules:

800FD	-	P	3	D	0	R	-	BP
I		II	III	IV	V	VI		VII

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type P – Pilot light
III.	Color Any number 0 through 9 is used to denote operator color
IV.	Lamp Style D – Incandescent N – LED
V.	Voltage / Lamp Any number 0 through 9 is used to denote lamp and voltage
VI.	Type of Wire Termination Blank – For Stripped Wire R – For Ring Lug
VII.	Packing Options Letters may be used to denote packaging options

Notes:

- The explanation of catalog numbers above is only for reference of standard options, if any more configuration of catalog numbers for customized options existed, they will be covered by this certification if the configuration, material specification and electrical specification keeps same conditions.*
- Rockwell Automation's plant code is 5010/5020.*

注: 此附录与自我声明同时使用时有效。