

## EU Declaration of Conformity

---

**Product:** *IEC Contactors, Safety Contactors, Reversing Contactors, Safety Reversing Contactors and Accessories*

---

*Name and address of the manufacturer:*  
**Sprecher + Schuh**  
*15910 International Plaza Drive*  
*Houston, TX 77032*  
*U.S.A.*

*Name and address of the authorised representative:*  
**Rockwell Automation NV**  
*Pegasus Park*  
*De Kleetlaan 12A*  
*1831 Diegem*  
*Belgium*

---

*This declaration of conformity is issued under the sole responsibility of the manufacturer.*

---

*Object of the declaration:* **Sprecher + Schuh CA7, CAS7, CAQ7, CAU7, CASU7 Series and Accessories**  
*(reference the attached list of catalogue numbers)*

---

*The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:*

<i>2014/35/EU</i>	<i>Low Voltage Directive</i>	<i>(LVD)</i>
<i>2014/30/EU</i>	<i>EMC Directive</i>	<i>(EMC)</i>
<i>2011/65/EU (incorporating 2015/863)</i>	<i>RoHS Directive</i>	<i>(RoHS)</i>

---

*References to the relevant harmonised standards used or references to the other technical specifications in relation to which conformity is declared:*

<i>EN IEC 60947-4-1:2019+AC:2020-05</i>	<i>Low-voltage switchgear and controlgear – Part 4-1: Contactors and motor-starters – Electromechanical contactors and motor-starters</i>
<i>EN 60947-5-1:2017+AC:2020-05</i>	<i>Low-voltage switchgear and controlgear – Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices</i>
<i>EN 60947-5-4:2003+A1:2019</i>	<i>Low-voltage switchgear and controlgear – Part 5-4: Control circuit devices and switching elements – Method of assessing the performance of low energy contacts – Special tests</i>
<i>EN IEC 63000:2018</i>	<i>Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances</i>

---

*Signed for and on behalf of the above named manufacturer:*

*Place and date of issue:* *Aarau, Switzerland* *21-Jun-2023*

*Name, function:* *Daniel Baumann, Manager – Product Compliance Engineering*

*Signature:* *i.V. Daniel Baumann*

---

Catalogue number	Series <sup>1</sup>	Description	Directive <sup>2</sup>		
			EMC	LVD	RoHS
CA*7-****_*_***		IEC Contactors with conventional coil per Nomenclature	N/R	Yes	Yes
CA*7-***E-_*_***		IEC Contactors with electronically-controlled DC coil per Nomenclature	Yes	Yes	Yes
<b>Accessories</b>					
C*(S)7-(R)P**_*_***		Auxiliary Contact Blocks per Nomenclature	N/R	Yes	Yes
CZ*7-*		Pneumatic Timing Modules per Nomenclature	N/R	N/R	Yes
CRZ*7-_*_*		Electronic Timing Modules per Nomenclature	Yes	Yes	Yes
CM7-_*_*		Mechanical Interlocks per Nomenclature	N/R	Yes	Yes
CV7-_*_*		Mechanical Latches per Nomenclature	N/R	Yes	Yes
CR*7-_*_***		Suppressor Modules per Nomenclature	N/R	Yes	Yes
CRI7E-*		Electronic DC Interfaces per Nomenclature	Yes	Yes	Yes
CAUT7-PW23 CAUT7-PW37 CAUT7-PW43 CAUT7-PW55 CAUT7-PW85		Reversing Power Wiring Kits	N/R	N/R	Yes
CAYT7-PW23 CAYT7-W37 CAYT7-PW43 CAYT7-PW55 CAYT7-PW72 CAYT7-PW85		Wye-Delta/Star-Delta Starter Wiring Kits	N/R	N/R	Yes
CA7-P-K**		Terminal Lug Kits per Nomenclature	N/R	Yes	Yes
CA7-P-B*		Paralleling Links per Nomenclature	N/R	Yes	Yes
CA7-SC2 CA7-SC10 CA4-SC11		Stab Connectors	N/R	N/R	Yes
CA7-SCC CA7-SCF		Protective Covers	N/R	N/R	Yes
CA7-S9		Dovetail Connector	N/R	N/R	Yes
CA7-FMS CA7-FMP CA7-FMC CA7-FMA2		Marking Systems	N/R	N/R	Yes

- 1) If no series number is given, then all series are covered.
- 2) Yes = Product is certified to this directive.  
N/R = This directive is not required for this product.

MODEL NOMENCLATURE:

***IEC Contactors, Safety Contactors, Reversing Contactors, Safety Reversing Contactors Catalogue Number Explanation***

<b>CA7</b>	-		<b>12</b>		<b>E</b>	-	<b>10</b>	-	<b>U</b>	<b>110E</b>	
<b>1</b>		<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>		<b>6</b>		<b>7</b>	<b>8</b>	<b>9</b>

<i>Position</i>	<i>Catalogue No. Suffix</i>	<i>Options/Descriptions</i>
<i>1</i>	<i>CA7 CAS7 CAQ7 CAU7 CASU7</i>	<i>Base Catalogue Number IEC Contactor (3-poles and 4-poles) IEC Safety Contactor (3-poles and 4-poles) IEC Capacitor Switching Contactor (3-poles, Contactor sizes 16 and 37) IEC Reversing Contactor (3-poles) IEC Safety Reversing Contactor (3-poles)</i>
<i>2</i>	<i>No suffix R</i>	<i>Terminal Type Screw terminals Spring force terminals</i>
<i>3</i>	<i>9, 12, 16, 23 30, 37, 40 43, 55 60, 72, 85, 90, 97</i>	<i>Contactor Size Frame size 0 Frame size 1 Frame size 2 Frame size 3</i>
<i>4</i>	<i>No suffix S</i>	<i>Special Features No special feature Coil with three field wiring terminals (for Contactor sizes 9, 12, 16, 23, 30, 37)</i>
<i>5</i>	<i>No suffix C D E</i>	<i>Coil Specification Designates conventional AC coil Designates conventional DC coil Designates conventional DC coil with integrated bi-directional diode between coil terminals Designates electronically-controlled DC coil</i>
<i>6</i>	<i>00, 01, 10 M22, M31, M40</i>	<i>Contact Configuration of Contactors (3-poles) Contact Configuration of Contactors (4-poles)</i>
	<i>02, 03, 04, 05, 11, 12, 13, 14, 21, 22, 23, 31, 32, 41, 204, 222, 302, 304, 311, 313, 322, 331, 402, 404, 405, 411, 413, 414, 422, 423, 431, 432</i>	<i>Contact Configuration of Safety Contactors Numbers followed by letter "C": Standard moveable contacts Numbers followed by letters "BC": Bifurcated moveable contacts</i>
	<i>11, 20</i>	<i>Contact Configuration of Capacitor Switching Contactors</i>
	<i>02, 22</i>	<i>Contact Configuration of Reversing Contactors</i>
	<i>08, 010, 012, 210</i>	<i>Contact Configuration of Safety Reversing Contactors Numbers followed by letter "C": Standard moveable contacts Numbers followed by letters "BC": Bifurcated moveable contacts</i>
<i>7</i>	<i>No suffix U</i>	<i>Coil Terminals Position Line side coil terminals Load side coil terminals (bottom)</i>

***IEC Contactors, Safety Contactors, Reversing Contactors, Safety Reversing Contactors Catalogue Number Explanation  
(continued)***

<b><i>Position</i></b>	<b><i>Catalogue No. Suffix</i></b>	<b><i>Options/Descriptions</i></b>
8	<i>One, two or three digits, optionally followed by one or two letters</i>	<p><i>Control Voltage Coil Code (designates coil-voltage and -frequency)</i></p> <p><i>AC coil code (conventional AC coil: 12...550V50Hz; 12...600V60Hz; 24...440V50/60Hz). Two or three digits, optionally followed by "A", "B", "W" or "Z"</i></p> <p><i>DC coil code (conventional DC coil: 9...250VDC). One, two or three digits followed by "C", "D"; additional suffix "D" designates integrated bi-directional diode between coil terminals, additional suffix "S" designates integrated suppressor between coil terminals</i></p> <p><i>DC coil code (electronically-controlled DC coil: 12...250VDC). Two or three digits followed by "E" (Contactor sizes 9, 12, 16, 23, 30, 37, 40, 43, 55)</i></p> <p><i>DC coil code (electronically-controlled DC coil with reduced drop-out time: 12...250VDC). Two or three digits followed by "Q" (Contactor sizes 9, 12, 16, 23, 30, 37, 40, 43, 55)</i></p>
9	<p><i>No suffix</i></p> <p><i>-X2</i></p> <p><i>-X3</i></p> <p><i>-F15</i></p> <p><i>-F16</i></p> <p><i>-X6</i></p>	<p><i>Options</i></p> <p><i>No option</i></p> <p><i>Control wiring provided (Reversing Contactors only)</i></p> <p><i>Terminal Covers not provided</i></p> <p><i>Spade connectors provided (Contactors only)</i></p> <p><i>Spade connectors provided (Contactors only)</i></p> <p><i>Spade connectors provided (Reversing Contactors only)</i></p>

*Accessories Catalogue Number Explanation*

**A.) Auxiliary Contact Blocks**

<b>CS7-P</b>	<b>V</b>		<b>-</b>	<b>L</b>		<b>22</b>
<b>1</b>	<b>2</b>	<b>3</b>		<b>4</b>	<b>5</b>	<b>6</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CA7-P, CS7-P CA7-RP, CS7-RP CAS7-P, CSS7-P CAS7-RP, CSS7-RP	Base Catalogue Number Auxiliary Contact Block with screw terminals Auxiliary Contact Block with spring force terminals Safety Auxiliary Contact Block with screw terminals Safety Auxiliary Contact Block with spring force terminals
2	A V	Mounting Position Side mounting Front mounting
3	No suffix B	Kind of Contact Auxiliary Contact Block with standard moveable contacts Auxiliary Contact Block with bifurcated moveable contacts
4	No suffix L LL	Contact Configuration Standard contacts One early make N.O. contact and one late break N.C. contact Two early make N.O. contacts and two late break N.C. contacts
5	No suffix S H	Options No option Terminal identification according to European standards One pole special purpose Auxiliary Contact (for use with Contactor sizes 9, 12, 16, 23, 30, 37)
6	Two digits	Contact Configuration First digit designates number of N.O. contacts Second digit designates number of N.C. contacts

**B.) Pneumatic Timing Modules**

<b>CZA7</b>	<b>-</b>	<b>30</b>
<b>1</b>		<b>2</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CZA7 CZE7	Base Catalogue Number Pneumatic Timing Module, off-delay Pneumatic Timing Module, on-delay
2	30 180	Time Range 0.3...30s 1.8...180s

*Accessories Catalogue Number Explanation (continued)*

**C.) Electronic Timing Modules**

<b>CRZA7</b>	<b>-</b>	<b>180</b>	<b>-24VAC</b>
<b>1</b>		<b>2</b>	<b>3</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CRZA7 CRZE7 CRZY7	Base Catalogue Number Electronic Timing Module, off-delay Electronic Timing Module, on-delay Electronic Timing Module, wye-delta
2	3  30 180	Time Range 0.1...3s (for CRZE7) 0.3...3s (for CRZA7) 1...30s 10...180s
3	No suffix  -24VAC -24VDC	Operation Voltage Code (designates coil-voltage and -frequency) 110...240V50/60Hz and 110...250VDC (for CRZE7) 110...240V50/60Hz (for CRZA7 and CRZY7) 24V50/60Hz (for CRZA7) 24...48VDC (for CRZE7)

**D.) Mechanical Interlocks**

<b>CM7</b>		<b>-02</b>
<b>1</b>	<b>2</b>	<b>3</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CM7	Base Catalogue Number of Mechanical Interlock
2	No suffix -S -T	Terminal Designation 21-22, 21-22 or none (no contacts provided) 55-56, 65-66 21-22, 31-32
3	No suffix -02	Contact Configuration No contacts provided Two N.C. contacts provided

**E.) Mechanical Latches**

<b>CV7</b>	<b>-</b>	<b>11</b>	<b>-</b>	<b>48Z</b>
<b>1</b>		<b>2</b>		<b>3</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CV7	Base Catalogue Number of Mechanical Latch
2	11	Contact Configuration One N.C. contact and one N.O. contact
3	Two or three digits, followed by an optional letter	Control Voltage Coil Code (designates coil-voltage and -frequency) AC coil code (conventional AC coil: 12...550V50Hz) AC coil code (conventional AC coil: 12...600V60Hz) AC coils may also be used for DC control voltages (special rules must be applied)

*Accessories Catalogue Number Explanation (continued)*

**F.) Suppressor Modules**

<b>CRC7</b>	<b>-R</b>	<b>-280</b>	
<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CRC7 CRD7 CRV7	Base Catalogue Number Suppressor Module, RC Module Suppressor Module, Diode Module Suppressor Module, Varistor Module
2	No suffix R	Terminal Type For Contactors with screw terminals For Contactors with spring force terminals
3	Two or three digits	Designates voltage range
4	No suffix W	Designates that Suppressor Module is provided with connectors which fit to the coil terminal of the Contactors Designates that Suppressor Module is provided with wire leads for connection to the coil terminal of the Contactors

**G.) Electronic DC Interfaces**

<b>CR17E</b>	<b>-</b>	<b>24</b>
<b>1</b>		<b>2</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CR17E	Base Catalogue Number of Electronic DC Interface
2	12 24 48	Operation Voltage Code (designates coil-voltage and -frequency) Input voltage 6...12VDC; output voltage 110...240V50/60Hz Input voltage 24VDC; output voltage 110...240V50/60Hz Input voltage: 35...48VDC; output voltage 110...240V50/60Hz

**H.) Terminal Lug Kits**

<b>CA7-P-K</b>	<b>N</b>	<b>23</b>
<b>1</b>	<b>2</b>	<b>3</b>

<b>Position</b>	<b>Catalogue No. Suffix</b>	<b>Options/Descriptions</b>
1	CA7-P-K	Base Catalogue Number of Terminal Lug Kit
2	No suffix N L	Connection Side Both sides Line side connection (only for CA7-P-KN23) Load side connection (only for CA7-P-KL23)
3	23 37 43 85	Max. AC-I Current 45A 60A 90A 130A

*Accessories Catalogue Number Explanation (continued)*

*I.) Paralleling Links*

<b>CA7-P-B</b>	<b>37</b>
<b>1</b>	<b>2</b>

<i>Position</i>	<i>Catalogue No. Suffix</i>	<i>Options/Descriptions</i>
<i>1</i>	<i>CA7-P-B</i>	<i>Base Catalogue Number of Paralleling Link</i>
<i>2</i>	<i>23</i> <i>37</i>	<i>Max. AC-1 Current</i> <i>100A</i> <i>150A</i>