
Non-Reversing, Three Pole Contactors With Two Winding DC Coil, Series CA7 (Open type only) ❶

I_e [A]		Ratings for Switching AC Motors (AC2 / AC3 / AC4)										Auxiliary Contacts per Contactor ❶		Open Type
		kW (50 Hz)				UL/CSA HP (60 Hz)								
						1 Ø		3 Ø						
AC-3	AC-1	230V	400V/ 415V	500V	690V	115V	230V	200V	230V	460V	575V	NO	NC	Catalog Number
60	100	18.5	32	37	32	**5**	**10**	**15**	**20**	**40**	**50**	0	0	**CA7-60D-00-✱**
												1	0	**CA7-60D-10-✱**
												0	1	**CA7-60D-01-✱**
72	100	22	40	45	40	**5**	**15**	**20**	**25**	**50**	**60**	0	0	**CA7-72D-00-✱**
												1	0	**CA7-72D-10-✱**
												0	1	**CA7-72D-01-✱**
85	100	25	45	55	45	**7-1/2**	**15**	**25**	**30**	**60**	**60**	0	0	**CA7-85D-00-✱**
												1	0	**CA7-85D-10-✱**
												0	1	**CA7-85D-01-✱**
97	130	30	55	55	55	**10**	**20**	**30**	**30**	**75**	**75**	0	0	**CA7-97D-00-✱**
												1	0	**CA7-97D-10-✱**
												0	1	**CA7-97D-01-✱**



CA7-60D Contactor

Description:
Contactors with two winding DC coils have very low hold-in values and share the same dimensions with AC contactors. See page A2:8 for more information. See page A2:59 for dimensional information.

Non-Reversing, Four Pole Contactors With Two Winding DC Coil, Series CA7 (Open type only) ❶

I_e [A]		Ratings for Switching AC Motors (AC2 / AC3 / AC4)										Contact Configuration Main Pole		Auxiliary Contacts per Contactor		Open Type
		kW (50 Hz)				UL/CSA HP (60 Hz)										
						1 Ø		3 Ø								
AC-3	AC-1	230V	415V 400V	500V	690V	115V	230V	200V	230V	460V	575V	NO	NC	NO	NC	Catalog Number
85	130	25	45	55	45	7-1/2	15	25	30	60	50	4	0	0	0	**CA7-90D-M40-✱**
85	130	25	45	55	18.5	7-1/2	15	25	30	50	20	2	2	0	0	**CA7-90D-M22-✱**

Coil Codes ❷❸

DC Coil Code	Voltage
24DD	24V
110DD	110V
220DD	220V

Ordering Instructions

Specify Catalog Number	
Replace (✱) with Coil Code	See Coil Codes on this page.

❶ CA7-60D...CA7-97D have an internal auxiliary contact to transition from the start winding to the run winding.
❷ Coils include an integrated diode surge suppressor.
❸ Other coil voltages are available, see page A2:29. Contact your Sprecher + Schuh Sales Representative to determine which coil voltages may be stocked.