

Single Phase, Non-Reversing CBTN7 @ 120V AC Non-Combination

NEMA Size	Max HP 1-Phase ①	Auxiliary Contacts per Contactor ②		Type 1 Metallic General Purpose ③	Price ④	DIM	Type 3R Metallic Outdoor Raintight	Price ④	DIM
		NO	NC	Catalog No.			Catalog No.		
00	0.33	2	1	CBTN7-12-120-ERB-G17-L11	824.75	A	CBTN7-12-120-ERB-R17-L11	1,174.28	L
0	0.5	2	1	CBTN7-16-120-ESB-G17-L11	864.61	A	CBTN7-16-120-ESB-R17-L11	1,214.14	L
	0.75	2	1	CBTN7-16-120-ESB-G17-L11	864.61	A	CBTN7-16-120-ESB-R17-L11	1,214.14	L
	1	2	1	CBTN7-16-120-ESB-G17-L11	864.61	A	CBTN7-16-120-ESB-R17-L11	1,214.14	L
1	1.5	2	1	CBTN7-37-120-ETD-G17-L11	1,088.43	A	CBTN7-37-120-ETD-R17-L11	1,463.50	L
	2	2	1	CBTN7-37-120-ETD-G17-L11	1,088.43	A	CBTN7-37-120-ETD-R17-L11	1,463.50	L
2	3	2	1	CBTN7-43-120-ETD-G17-L11	1,261.15	A	CBTN7-43-120-ETD-R17-L11	1,686.30	L
3	5	2	1	CBTN7-85-120-EUE-G17-L11	1,717.98	B	CBTN7-85-120-EUE-R17-L11	2,145.18	M
	7.5	2	1	CBTN7-85-120-EUE-G17-L11	1,717.98	B	CBTN7-85-120-EUE-R17-L11	2,145.18	M

Full Voltage Non-Reversing (FVNR) Features include:


- NEMA-sized CAN7 contactor
- Single-Phase CEP7S electronic overload relay
- AC coil
- Hand-Off-Auto (H-O-A) selector switch
- Red Run pilot light
- 2-NO and 1-NC auxiliaries for customer use
- Reset pushbutton

Single Phase, Non-Reversing CBTN7 @ 230V AC Non-Combination

NEMA Size	Max HP 1-Phase ①	Auxiliary Contacts per Contactor ②		Type 1 Metallic General Purpose ③	Price ④	DIM	Type 3R Metallic Outdoor Raintight	Price ④	DIM
		NO	NC	Catalog No.			Catalog No.		
00	0.25	2	1	CBTN7-12-220W-EPB-G17-L11	824.75	A	CBTN7-12-220W-EPB-R17-L11	1,174.28	L
	0.5	2	1	CBTN7-12-220W-ERB-G17-L11	824.75	A	CBTN7-12-220W-ERB-R17-L11	1,174.28	L
	0.75	2	1	CBTN7-12-220W-ERB-G17-L11	824.75	A	CBTN7-12-220W-ERB-R17-L11	1,174.28	L
	1	2	1	CBTN7-12-220W-ERB-G17-L11	824.75	A	CBTN7-12-220W-ERB-R17-L11	1,174.28	L
0	1.5	2	1	CBTN7-16-220W-ESB-G17-L11	864.61	A	CBTN7-16-220W-ESB-R17-L11	1,214.14	L
	2	2	1	CBTN7-16-220W-ESB-G17-L11	864.61	A	CBTN7-16-220W-ESB-R17-L11	1,214.14	L
1	3	2	1	CBTN7-37-220W-ETD-G17-L11	1,088.43	A	CBTN7-37-220W-ETD-R17-L11	1,463.50	L
2	5	2	1	CBTN7-43-220W-ETD-G17-L11	1,261.15	A	CBTN7-43-220W-ETD-R17-L11	1,463.50	L
	7.5	2	1	CBTN7-43-220W-ETD-G17-L11	1,261.15	A	CBTN7-43-220W-ETD-R17-L11	1,686.30	L
3	10	2	1	CBTN7-85-220W-EUE-G17-L11	1,717.98	B	CBTN7-85-220W-EUE-R17-L11	2,145.18	M
	15	2	1	CBTN7-85-220W-EUE-G17-L11	1,717.98	B	CBTN7-85-220W-EUE-R17-L11	2,145.18	M

Full Voltage Non-Reversing (FVNR) Features include:

- NEMA-sized CAN7 contactor
- Single-Phase CEP7S electronic overload relay
- AC coil
- Hand-Off-Auto (H-O-A) selector switch
- Red Run pilot light
- 2-NO and 1-NC auxiliaries for customer use
- Reset pushbutton



This item is available in the **ORANGE EXPRESS** 3-day shipping program

- ① HP and NEMA size selection shown for 120V ratings only. Contact your Sprecher + Schuh representative for other voltage applications.
- ② Contactors are equipped with number and type of auxiliaries indicated. See page C108 to order additional or different auxiliary contacts.
- ③ Dimensional information starts on page C122.
- ④ HP and NEMA size selection shown for 230V ratings only. Contact your Sprecher + Schuh representative for other voltage applications.