

Series CATN7 with Thermal-Magnetic Circuit Breaker

NEMA Size	Maximum Horsepower Three Phase				MCCB Amps	Type 1 General Purpose	D I M	Type 12 [Type 3R Ⓣ] Industrial Dusttight	D I M	Type 4 Watertight	D I M	Type 4X Watertight Corrosion Resistant Non-metallic	D I M
	200V	230V	460V	575V		Catalog No.		Price ①		Catalog No.		Price ①	
						CATN		CATN		CATN		CATN	
00	1-1/2	1-1/2	2	2 Ⓣ	15	7-12-*◆-TB15G0 ⓧ	1320 C2	7-12-*◆-TB15D0 ⓧ	1533 C3	7-12-*◆-TB15W0	2256 C2	7-12-*◆-TB15C0 ⓧ	1703 V2
	2	2	5	5 Ⓣ	15	7-16-*◆-TB15G0 ⓧ	1362 C2	7-16-*◆-TB15D0 ⓧ	1575 C3	7-16-*◆-TB15W0	2299 C2	7-16-*◆-TB15C0 ⓧ	1746 V2
	3	3	~	~	20	7-16-*◆-TB20G0 ⓧ	1362 C2	7-16-*◆-TB20D0 ⓧ	1575 C3	7-16-*◆-TB20W0	2299 C2	7-16-*◆-TB20C0 ⓧ	1746 V2
1	~	~	7-1/2	10 Ⓣ	20	7-37-*◆-TB20G0 ⓧ	1575 C2	7-37-*◆-TB20D0 ⓧ	1831 C3	7-37-*◆-TB20W0	2512 C2	7-37-*◆-TB20C0 ⓧ	1958 V2
	~	5	10	~	30	7-37-*◆-TB30G0 ⓧ	1575 C2	7-37-*◆-TB30D0 ⓧ	1831 C3	7-37-*◆-TB30W0	2512 C2	7-37-*◆-TB30C0 ⓧ	1958 V2
	5	~	~	~	35	7-37-*◆-TB35G0 ⓧ	1575 C2	7-37-*◆-TB35D0 ⓧ	1831 C3	7-37-*◆-TB35W0	2512 C2	7-37-*◆-TB35C0 ⓧ	1958 V2
	~	7-1/2	~	~	40	7-37-*◆-TB40G0 ⓧ	1575 C2	7-37-*◆-TB40D0 ⓧ	1831 C3	7-37-*◆-TB40W0	2512 C2	7-37-*◆-TB40C0 ⓧ	1958 V2
	7-1/2	~	~	~	50	7-37-*◆-TB50G0 ⓧ	1575 C2	7-37-*◆-TB50D0 ⓧ	1831 C3	7-37-*◆-TB50W0	2512 C2	7-37-*◆-TB50C0 ⓧ	1958 V2
2	~	~	~	15 Ⓣ	35	7-43-*◆-TB35G0 ⓧ	1618 C2	7-43-*◆-TB35D0 ⓧ	2044 C3	7-43-*◆-TB35W0	2555 C2	7-43-*◆-TB35C0 ⓧ	2214 V2
	~	~	15	20 Ⓣ	40	7-43-*◆-TB40G0 ⓧ	1618 C2	7-43-*◆-TB40D0 ⓧ	2044 C3	7-43-*◆-TB40W0	2555 C2	7-43-*◆-TB40C0 ⓧ	2214 V2
	~	10	20	25 Ⓣ	50	7-43-*◆-TB50G0 ⓧ	1618 C2	7-43-*◆-TB50D0 ⓧ	2044 C3	7-43-*◆-TB50W0	2555 C2	7-43-*◆-TB50C0 ⓧ	2214 V2
	10	~	25	~	60	7-43-*◆-TB60G0 ⓧ	1618 C2	7-43-*◆-TB60D0 ⓧ	2044 C3	7-43-*◆-TB60W0	2555 C2	7-43-*◆-TB60C0 ⓧ	2214 V2
	~	15	~	~	80	7-43-*◆-TB80G0 ⓧ	1618 C2	7-43-*◆-TB80D0 ⓧ	2044 C3	7-43-*◆-TB80W0	2555 C2	7-43-*◆-TB80C0 ⓧ	2214 V2
3	~	~	~	30 Ⓣ	60	7-85-*◆-TB60G0 ⓧ	1831 D3	7-85-*◆-TB60D0 ⓧ	3243 Q	7-85-*◆-TB60W0	3322 Q	7-85-*◆-TB60C0 ⓧ	2427 W2
	~	~	30	40 Ⓣ	80	7-85-*◆-TB80G0 ⓧ	1831 D3	7-85-*◆-TB80D0 ⓧ	3243 Q	7-85-*◆-TB80W0	3322 Q	7-85-*◆-TB80C0 ⓧ	2427 W2
	15	20	40	50 Ⓣ	100	7-85-*◆-TB100G0 ⓧ	1831 D3	7-85-*◆-TB100D0 ⓧ	3243 Q	7-85-*◆-TB100W0	3322 Q	7-85-*◆-TB100C0 ⓧ	2427 W2
	25	30	50	~	125	7-85-*◆-TB125G0 ⓧ	1831 D3	7-85-*◆-TB125D0 ⓧ	3243 Q	7-85-*◆-TB125W0	3322 Q	7-85-*◆-TB125C0 ⓧ	2427 W2

C
NEMA Combination Starters

 This item is available in the **ORANGE EXPRESS** 3-day shipping program

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See page C104 See pages C105-C106 See pages C107-C111
Replace (◆) with O/L Relay	
Factory Modifications available	

NOTE: Catalog numbers and enclosure dimensions reflect contactors with AC coils. For DC coils, select Coil Code from the DC Coil Code table on page C104 and follow the instructions for modifying catalog numbers.

- ① Dimensional information starts on page C122.
- ② For Type 3R outdoor applications, replace "D" in catalog number with an "R". Dimensions may change. For example number CATN7-37-*◆-TB40D0 becomes CATN7-37-*◆-TB40R0. Price remains the same.
- ③ Applicable to 600Y/347V only. Refer to page C70 for 600V Delta solution.