

Autotransformer 150 HP to 1000 HP (Closed Transition - Type 1 General Purpose Enclosure) ④

Maximum H.P.	3 Ø Volts	Without Short Circuit Protection			With Thermal Magnetic Circuit Breaker (MCCB)			Fuse Clip Amps	With Fusible Disconnect ②⑤			
		Catalog No.	Price ①	D I M	MCCB Amps	Catalog No.	Price ①		D I M	Catalog No.	Price ①	D I M
		CAAT				CAAT				CAAT		
150	200	NA9-460-EI-♦-◆-G0	45681	J2	800	NA9-460-EI-♦-◆-TB800G0	60873	R/F	800	NA9-460-EI-♦-◆-JF67G0	61264	~
	230	NB9-370-♦-◆-G0 ⑥	42532	J2	700	NB9-370-♦-◆-TB700G0 ⑥	54695	K2	600	NB9-370-♦-◆-JF66G0 ⑥	59539	K2
	460	NC9-205-♦-◆-G0 ⑥	33096	I	350	NC9-205-♦-◆-TB350G0 ⑥	43228	J	400	NC9-205-♦-◆-JF65G0 ⑥	40099	K3
	575	ND9-190-♦-◆-G0 ⑥	20718	I	300	ND9-190-♦-◆-TB300G0 ⑥	25798	J	400	ND9-190-♦-◆-JF65G0 ⑥	26449	K3
200	230	OB9-460-EI-♦-◆-G0	45681	~	1000	OB9-460-EI-♦-◆-TB1000G0	60873	~	800	OB9-460-EI-♦-◆-JF67G0	61264	~
	460	OC9-265-♦-◆-G0 ⑥	33507	J	450	OC9-265-♦-◆-TB450G0 ⑥	43688	K2	400	OC9-265-♦-◆-JF65G0 ⑥	39443	K2
	575	OD9-205-♦-◆-G0 ⑥	33096	J	350	OD9-205-♦-◆-TB450G0 ⑥	43228	K2	400	OD9-205-♦-◆-JF65G0 ⑥	40099	K3
250	230	PB9-580-EI-♦-◆-G0	R/F	~		Refer to Factory	R/F	~		Refer to Factory	R/F	~
	460	PC9-305-♦-◆-G0 ⑥	36984	J2	600	PC9-305-♦-◆-TB600G0 ⑥	47561	K2	600	PC9-305-♦-◆-JF66G0 ⑥	51773	K2
	575	PD9-265-♦-◆-G0 ⑥	33507	J	450	PD9-265-♦-◆-TB450G0 ⑥	43688	K2	400	PD9-265-♦-◆-JF65G0 ⑥	39443	K2
300	230	QB9-750-EI-♦-◆-G0	R/F	~		Refer to Factory	R/F	~		Refer to Factory	R/F	~
	460	QC9-370-♦-◆-G0 ⑥	42532	J2	700	QC9-370-♦-◆-TB700G0 ⑥	54695	K2	600	QC9-370-♦-◆-JF66G0 ⑥	59539	K2
	575	QD9-305-♦-◆-G0 ⑥	36984	J2	600	QD9-305-♦-◆-TB600G0 ⑥	47561	K2	600	QD9-305-♦-◆-JF66G0 ⑥	51773	K2
350	230	Refer to Factory	R/F	~		Refer to Factory	R/F	~		Refer to Factory	R/F	~
	460	RC9-400-EI-♦-◆-G0	37753	J2	800	RC9-400-EI-♦-◆-TB800G0	50308	RF	800	RC9-400-EI-♦-◆-JF67G0	50631	~
	575	RD9-370-♦-◆-G0 ⑥	42532	J2	600	RD9-370-♦-◆-TB600G0 ⑥	54695	K2	600	RD9-370-♦-◆-JF66G0 ⑥	59539	K2
400	230	Refer to Factory	R/F	~		Refer to Factory	R/F	~		Refer to Factory	R/F	~
	460	SC9-460-EI-♦-◆-G0	45681	~	1000	SC9-460-EI-♦-◆-TB1000G0	60873	~	800	SC9-460-EI-♦-◆-JF67G0	61264	~
	575	SD9-400-EI-♦-◆-G0	37753	J2	700	SD9-400-EI-♦-◆-TB700G0	50308	K2	600	SD9-400-EI-♦-◆-JF66G0	50631	~
450	230	Refer to Factory	R/F	~		Refer to Factory	R/F	~		Refer to Factory		
	460	TC9-580-EI-♦-◆-G0	59386	~		Refer to Factory	R/F	~				
	575	TD9-460-EI-♦-◆-G0	45681	~	800	TD9-460-EI-♦-◆-TB800G0	60873	~				
500	460	UC9-580-EI-♦-◆-G0	59386	~		Refer to Factory	R/F	~				
	575	UD9-460-EI-♦-◆-G0	45681	~	900	Refer to Factory	R/F	~				
600	460	UC9-750-EI-♦-◆-G0	77796	~		Refer to Factory	R/F	~				
	575	UD9-580-EI-♦-◆-G0	59386	~		Refer to Factory	R/F	~				

Larger sizes available. Contact your Sprecher + Schuh representative.

NOTE: Catalog numbers and enclosure dimensions reflect contactors with AC coils. For DC coils, select Coil Code from the DC Coil Code table on page C104 and follow the instructions for modifying catalog numbers.

Ordering Instructions

Specify Catalog Number	
Replace (*) with Coil Code	See page C104 SeepagesC105-C106 SeepagesC107-C111
Replace (◆) with O/L Relay	
Factory Modifications available	

- ① Dimensional information starts on page C122.
- ② For Non-fusible Disconnect applications, replace the "JF" characters with "JU".
Example: CAATNC9-205-EI-♦-◆-JF65G0 becomes CAATNC9-205-EI-♦-◆-JU65G0.
- ③ Fuse clips sized for use with "J"-type fuses up to 600A. Power fuses not supplied.
- ④ Other enclosures available. Contact your Sprecher + Schuh Representative.
- ⑤ A Red and Yellow Handle may be selected instead of the standard Gray and Black handle. Change "JF" to "LF" in catalog number.
- ⑥ CAT9-116...CAT9-370 starters are available with "EI" option for PLC interface. Change catalog number to include "-EI". For example: CAATND9-190-♦-◆-G0 becomes CAATND9-190-EI-♦-◆-G0. See page C104 for price adder.