

Classic Handle Assembly, Type 1/4/4X/12

Accessory	Description	Color	Legend	For use with	Frame Size (Length)	Catalog Number
TRUE ION	Classic Door Coupling Handle ● For 3 padlocks 48 mm (5/16") diameter Type 1/3/3R/4/4X/12 and IP66 Interlock override capability Can be modified for locking in ON position Ships with coupling — order extension shaft and legend plate separately See Technical Section for mounting depth information	Gray/ Black	O - I OFF -ON Trip	KT_9-32S, KT_9-40H, KTU9 ①	65 x 65mm	KT9-HTN
				KT_7-45H 		KT7-HTN
		Red/ Yellow	O - I OFF -ON Trip	KT_9-32S, KT_9-40H, KTU9 	65 x 65mm	KT9-HTRY
				KT_7-45H •		KT7-HTRY
	KT9-HTN KT9-HTRY	KT9-HTRV	КТ9-НТ			
	Extension Shaft • Cut to required length for mounting depth			KT7-HTN KT7-HTRY	250 mm	КТ7-НТ
	(front of DIN Rail to front of enclosure door)See Technical Section for mounting depth infor	mation	nation	KT9-HTN KT9-HTRY	400 mm	KT9-HTL
				KT7-HTN KT7-HTRY	400 11111	KT7-HTL

Contemporary Handle Assembly, Type 3R/3/4/4X

Accessory	Description	Color	Legend	For use with	Frame Size (Length)	Catalog Number
	Contemporary Door Coupling Handle Screw Fixing Type 3R, 3, 12, 4, 4X, IP66 Field configurable for defeatable or non-defeatable Ships with coupling — order extension shaft and legend plate separately Requires 30mm hole for mounting For up to 2 padlocks	Black/ Black	O - I OFF -ON Trip	KT_9-32S, KT_9-40H, KTU9	48.7 x 47mm	KT9-SB
				KT_7-45H		KT7-SB
		Red/ Yellow	O - I OFF - ON Trip	KT_9-32S, KT_9-40H, KTU9	. 48.7 x 47mm	KT9-SY
				KT_7-45H		KT7-SY
	Extension Shaft • Cut to required length for mounting depth			KT9-SB KT9-SY	305mm (12")	KT9-S1
				KT7-SB KT7-SY		KT7-S1
	(front of DIN Rail to front of enclosure door) • See Technical Section for mounting depth informa			KT9-SB KT9-SY	533mm	KT9-S2
				KT7-SB KT7-SY	(21")	KT7-S2

Handle Accessories

Accessory	Description	For use with	Catalog Number
	Coupler Coupler for extension short Included with KT9-SB/S	KTA9-32S, KT_9-40H KTU9-40H	KT9-DNC
Oiiii	Extension Shaft Support Provides consistent alignment of the shafts with handle or door coupling	KT_9-32S, KT_9-40H, KTU9	KT9-SHS
	Recommended for shaft lengths > 200mm (7.8 in) Final in width and snaps on right side of devices Allows for one side-mount auxiliary	KT_7-45H	KT7-SHS
HAUPTSCHAUER MAIN SWITCH NOT - AUS EMERBERCY - OFF		KT9-HT_	KT9-HTFCN
	Legend Plate • Marking: "Haupschalter" and "Main Switch" (Black/Gray) • Marking: "Not-Aus" and "Emergency Off" (Black/Yellow)	KT7-HT_	KT7-HTFCN
		KT9-HT_	KT9-HTFCRY
		KT7-HT_	KT7-HTFCRY

- See Dimensions and Technical data in this section for design compatibility.
 See page F41 for assembly example and dimensions.