

## Connecting Modules (for connecting KTA7, KTB7 or KTC7 into KT\_9 to CA8, CA7 AC coil, or CA7 Electronic DC coil contactors) 2

Module	Туре	Description	For Connecting	Catalog Number <b>0</b>
	ECO Connection Module 12A (IEC) , 11A (UL)	<ul> <li>For DOL and revering starters</li> <li>Eco-starters mount on single DIN Rail (KT_9 on DIN Rail)</li> <li>Electrical and mechanical interconnection of KT_9 and CA8 contractors</li> </ul>	KT_9-32S to CA8	KT9-32S-PEK12
	ECO Connection Module 25A (IEC) , 22A (UL)	Eco-starters mount on single DIN Rail (KT_9 on DIN Rail)     Electrical and mechanical interconnection of KT_9 MPCB and CA7 (with AC coils or 24V DC electronic coils) contactors	KT_9-32S to CA7-923	KT9-32S-PEC23
			KT_9-40H to CA7-923	KT9-40H-PEC23
	ECO Connection Module 38A (IEC) , 34A (UL)	<ul> <li>Eco-starters mount on single DIN Rail (KT_9 on DIN Rail)</li> <li>Electrical and mechanical interconnection of KT_9 MPCB and CA9 (with AC coils or 24V DC electronic coils) contactors</li> </ul>	KT_9 -40H to CA7-3037	KT9-40H-PEC37
	ECO Connection Module KT9PNC23 25A (IEC), 24A (UL) KT9PNC37 38A (IEC), 34A (UL)	Contactor and MPCB MUST BE mounted separately on (2) DIN Rails Electrical interconnection of KT_9 and CA7 (with AC coils)	KT_9-32S to CA7-923	KT9-32S-PNC23
×			KT_9-40H to CA7-923	KT9-40H-PNC23
			KT_9-40H to CA7-3037	KT9-40H-PNC37
	Connecting Modules — 25 and 45 A	Contactor and MPCB MUST BE mounted separately on (2) DIN Rails Electrical     Interconnection of KT_7-45H and CA7 (with AC coils)	KT_7-45H to CA7-3037	KT7-45H-PNC37
			KT_7-45H to CA7-43	KT7-45H-PNC43

## **Coil Modules**

$\sim$	Coil Extension Modules	Provides access to coil terminals on 3-component starters	CA7-923	KT9-32S-PSC23
Coil Exten			CA7-3055	KT9-80H-PSC43
n n A			CA7-3055	KT7-45H-PSC43

## Type W Mounting Modules

Module	Description		Catalog Number
	Short Mounting Module - Requires Connecting Module from tables above • Provides support for KT7 + CA7 or CA8 • Top rail is specifically designed for KT7 • Bottom rail is movable for easy assembly and disassembly • Complete unit mounts to two 35mm DIN-rails or one 70mm DIN-rail or screw mounts • 228 mm long	45	W-32489
		54	W-32490
	Long Mounting Module - See Section D for Connecting Modules • Provides support for KT7 + PCS Softstarter, CA7 + PCS Softstarter or KTB7 + CA7+CEP7 • Top rail is specifically designed for KT7 • Bottom rail is movable for easy assembly and disassembly • Complete unit mounts to two 35mm DIN-rails or one 70mm DIN-rail or screw mounts • 283 mm long	45	W-32496
		54	W-32497
Sales of the sales	Spacer for Mounting Module - Fits between 45mm and 54mm for Reversing applications (228 mm long)	9	W-32955
	Dovetail Joints - Used to connect two mounting modules tegether (Sold in packages of 50)		W-32954

- cURus Approved (File # E33916).
- Not for use with KTU9 Circuit Breakers