









CX7 KWIKstarter Enclosures for use with KTA9 Type E Motor Controllers and CA7 Contactors ①③

Component	Description	For Use With		Environmental Approvals	Catalog Number
		Type E Controller	Contactors		
	Enclosure for Combo KWIKstarter ① CX7/CXU7-9...23 CX7/CXU7-9E...23E	KTA9-32S KTA9-40H	CA7-9...23 CA7-9E...23E CAU7-9...23 CAU7-9E...23E	cUL Type 1/12K IEC IP66	KS7-C0C4R

Handle Accessory for CX7/CXU7 KWIKstarters ①

Accessory	Description	For Use With	Color	Catalog Number
	Door Coupling Handle ① • Padlockable • NEMA Type 1/12K and IP66 • Includes handle coupling (shaft) • Requires KT9-KN1 Locking Knob	All KT9s	Gray/Black Red/Yellow	T.B.A. T.B.A.
	Lockable Twist Knob • for use with KT9-SHB	All KT9s	Gray/Black	KT9-KN
	Universal Connector for CX7/CXU7 • Provides electrical interconnection of KTA9 and CA7 (with AC or Electronic DC coil) • Applies to FVNR and FVR versions • Allows for mounting the CA7 on a single DIN rail	All KT9s	Black	T.B.A. ④

CX7 KWIKstarter Pilot Device Kits (for use with KS7-C0C4R Type 1/12K) ①②⑥

Kits	Description	Contact Blocks included		Catalog Number
		NO	NC	
	Multi-Function Pushbutton kit Non-illuminated START-STOP I-O	1	1	KS7-P3U KS7-P4U
	FOR-STOP-REV UP-STOP-DOWN OPEN-STOP-CLOSE	2	1	KS7-P3U-REV KS7-P4U-REV KS7-P5U-REV
	Selector switch kits Non-illuminated, includes legend plate			
	ON-OFF 2-Position	1	0	KS7-P6
	HAND-OFF-AUTO 3-Position	2	0	KS7-P7
	FOR-OFF-REV 3-Position UP-OFF-DOWN 3-Position OPEN-OFF-CLOSE 3-Position	2	0	KS7-P6-REV KS7-P7-REV KS7-P8-REV
	Run Pilot Light or Overload Alarm Pilot Light Plastic operator with diffuser lens in Red, Green or Yellow, with integrated LED power module		Replace ⑤ with color choice R = Red G = Green Y = Yellow	KS7-P1⑤24V ⑥ KS7-P1⑤120V KS7-P1⑤240V
	Hole Plug used to plug 22.5mm holes.		Gray Plastic	D7-N8

- ① KS7-C0C4R is supplied with the following holes:
 - (1) one 22mm hole for a Pilot Device option, select one kit from this page.
 - (1) one 22mm hole for KT9-SHB (or SHRY) Disconnect or Reset handle.
- ② Plastic bezel is standard. Pilot Device Kits include D7-BX_ Base Mounted contact blocks. See Section H for more information.

- ③ CPT not possible.
- ④ Standard KT9-32S-PEC23 does not work in CX7/CXU7 Kwikstarters.
- ⑤ KS7-P1⑤24V can be used with 24VAC or 24VDC.
- ⑥ KS7-C0C4R series B enclosures compatible to KTA9 series controllers
KS7-C0C4R series A enclosures compatible to KTA9 series controllers