



M22 Panel Mount Alarm/LED Control Beacon



Type	Description	Specification	Catalog Number ①		Price
			Grey Housing	Black Housing	
Replace Ⓢ with lens color					
	ELG Panel Mount Alarm 65mm with LED Control Beacon (103 dB) Tone & light synchronized only Amber and Red Ⓢ	12 V AC/DC 24 V AC/DC 110/120 V AC 230/240 V AC	814 11Ⓢ 404 814 11Ⓢ 405 814 11Ⓢ 310 814 11Ⓢ 313	814 51Ⓢ 404 814 51Ⓢ 405 814 51Ⓢ 310 814 51Ⓢ 313	189.78
	ELM Panel Mount Alarm 45mm with LED Control Beacon (98 dB) Tone & light synchronized only Amber and Red Ⓢ	12 V AC/DC 24 V AC/DC 110/120 V AC 230/240 V AC	813 11Ⓢ 404 813 11Ⓢ 405 813 11Ⓢ 310 813 11Ⓢ 313	813 51Ⓢ 404 813 51Ⓢ 405 813 51Ⓢ 310 813 51Ⓢ 313	149.60
	EDG Panel Mount Alarm 65mm with LED Control Beacon (103 dB) Tone & light separately switchable only Amber and Red Ⓢ	12 V AC/DC 24 V AC/DC 110/120 V AC 230/240 V AC	814 12Ⓢ 404 814 12Ⓢ 405 814 12Ⓢ 310 814 12Ⓢ 313	814 52Ⓢ 404 814 52Ⓢ 405 814 52Ⓢ 310 814 52Ⓢ 313	260.43
	EDM Panel Mount Alarm 45mm with LED Control Beacon (98 dB) Tone & light separately switchable only Amber and Red Ⓢ	12 V AC/DC 24 V AC/DC 110/120 V AC 230/240 V AC	813 12Ⓢ 404 813 12Ⓢ 405 813 12Ⓢ 310 813 12Ⓢ 313	813 52Ⓢ 404 813 52Ⓢ 405 813 52Ⓢ 310 813 52Ⓢ 313	207.80
	Adapter M30.5			812 500 900	17.82
	Fastening tool M22 30mm			D7-AW2 See Section H	

M22 Panel Mount Sounders



Type	Description	Specification	Catalog Number		Price
			Grey Housing	Black Housing	
	ESK Panel Mount Alarm 30mm ④ Pulse/Continuous Tone 65 dBa Fully enclosed, smooth front ②	12...24V AC/DC 110/120V AC 230/240V AC	812 100 405 812 100 310 812 100 313	812 500 405 812 500 310 812 500 313	66.77
	ESV Panel Mount Alarm 30mm ④ Pulse/Continuous Tone 85 dBa Slotted housing, high output	12...24V AC/DC 110/120V AC 230/240V AC	812 110 405 812 110 310 812 110 313	812 510 405 812 510 310 812 510 313	66.77
	ESM Panel Mount Alarm 45mm Pulse/Continuous Tone <85-100 dBa ⑤ Slotted housing, high output	12...24V AC/DC 110/120V AC 230/240V AC	813 100 405 813 100 310 813 100 313	813 500 405 813 500 310 813 500 313	113.16
	ESG Panel Mount Alarm 65mm Pulse/Continuous/Wobble Tone <85-105 dBa ⑤ Slotted housing, high output	12...24V AC/DC 110/120V AC 230/240V AC	814 100 405 814 100 310 814 100 313	814 500 405 814 500 310 814 500 313	164.84

① To complete the catalog no., replace the Ⓢ with one of the following numbers for desired lens color:

1 = Amber, 2 = Red, 4 = Clear, 5 = Blue, 6 = Green, 7 = Yellow.

② No slots in the housing. Ideal for food industry environments.

③ Adjustable volume capabilities.

④ D7 Legend Plates can be used with the 30mm devices. Also, the mounting ring is the same as D7-ARP, which can be secured to a panel with use of the D7-AW2 mounting wrench. See Section H for D7 components.