

Switch Handle Assemblies (LA and LE Switches) ②

Switch Handle Assembly	Color	Mounting Method	Protection Rating	For use with...	Frame Size	Legend	Catalog Number
 Type G	Gray Frame Black Handle	Screw Fixing ①	Type 4/4X, IP66	LA/LE7-16	54 x 54	O — I OFF — ON	LFS7-G-4-175
			Type 4/4X, IP66	LA7-16...100A LE7-25...100A	67 x 67	O — I OFF — ON	LFS2-G-6-175
			Type 4/4X, IP66	LA/LE7-40...100A	90 x 90	O — I OFF — ON	LFS2-G-8-175 ⑥
		Central Nut	Type 12, IP66	LE7-16...63A	67 x 67	O — I OFF — ON	LFC2-G-6-175
 Type N	Yellow Frame Red Handle	Screw Fixing ①	Type 4/4X, IP66	LA/LE7-16	54 x 54	O — I OFF — ON	LFS7-N-4-175
			Type 4/4X, IP66	LA7-16...100A LE7-25...100A	67 x 67	O — I OFF — ON	LFS2-N-6-175
			Type 4/4X, IP66	LA/LE7-40...100A	90 x 90	O — I OFF — ON	LFS2-N-8-175 ⑥
		Central Nut	Type 12, IP66	LE7-16...63A	67x67	O — I OFF — ON	LFC2-N-6-175

Switch Handle Assemblies for LA7 Switches - Type 4/4X ①②③④⑤

Switch Handle Assembly	Mounting Method	Protection Rating	For use with...	Frame Size	Legend	Color	Catalog Number
 Type R	Screw Fixing Configurable for defeatable or non- defeatable	Type 3R, 3, 12, 4, 4X IP66	LA7-16...100A	48.7 x 47	O — I OFF — ON	Black Frame Black Handle	LA7-SB
		Type 3R, 3, 12, 4, 4X IP66		48.7 x 47	O — I OFF — ON	Yellow Frame Red Handle	LA7-SY
 Type R	Screw Fixing Configurable for defeatable or non- defeatable	Type 3R, 3, 12, 4, 4X	LA7-16...100A	80 x 114	O — I OFF — ON	Black Frame Black Handle	L11-PB
		Type 3R, 3, 12, 4, 4X		80 x 114	O — I OFF — ON	Yellow Frame Red Handle	L11-PY

① Mounting screws included with Switch Body Assembly.

② Lockable in OFF position with up to 3 padlocks.

③ For LA7 base mount switches only.

④ Switch handle can be field modified to be defeatable or non-defeatable.

⑤ Handles LA7-S_ and L11-P_ require R-type Switch Handle Shaft Extension. See page L1:13.

⑥ This handle cannot be used on a mechanical coupling accessory L2-G3* when coupling any LE7 switches. Must select smaller 48x48 or 64x64 type handles for LE7 coupling applications.