







Beacons G 120 mm ø CE

Type	Description	Specifications	Catalog Number ①	
			Grey Housing	Black Housing
	WLG Steady Beacon (no bulb) ②	up to 250 V AC/DC	822 10⊕ 900	822 50⊕ 900
	FLG Strobe Beacon (Xenon tube included)	24 V AC/DC, ~5 J 230/240 V AC, ~5 J	842 14⊕ 405 842 13⊕ 313	842 54⊕ 405 842 53⊕ 313
	DLG LED-Steady Beacon Amber, red and yellow only	24 V AC/DC 48 V AC/DC 110/120 V AC 230/240 V AC <i>(Only Clear, Green Blue 48V and 120V)</i>	827 10⊕ 405 827 10⊕ 408 827 10⊕ 310 827 10⊕ 313	827 50⊕ 405 827 50⊕ 408 827 50⊕ 310 827 50⊕ 313
	BLG LED-Flashing Beacon Amber, red and yellow only	24 V AC/DC 230/240 V AC	807 10⊕ 405 807 10⊕ 313	807 50⊕ 405 807 50⊕ 313
	Bracket for all "G" models		822 200 900	822 200 900

Strobe Beacons Z CE

Type	Description	Specifications		Catalog Number	
		Voltage/Strobe	Lens Color	Dark Grey Housing	
	BZG Strobe Beacon Xenon tube included	24 V DC, 15 J	Amber Red Yellow	741 041 005 741 042 005 741 047 005	
		230/240 V AC, 15 J	Amber Red Yellow	741 031 313 741 032 313 741 037 313	


① To complete the catalog no., replace the ⊕ with one of the following numbers for desired lens color:

1 = Amber, 2 = Red, 4 = Clear, 5 = Blue, 6 = Green, 7 = Yellow.


② Bulb not included. Order separately on page J39.




Strobe Beacon XB2 C €

Type	Description	Specifications	Catalog Number	
	Replace ☉ with lens color	Voltage/Strobe	Black Housing ❶	
	XB2 Strobe Beacon Xenon tube included Amber and red only	12 V DC, 2 J	D118 52☉ 004 ❷	
		24 V DC, 2 J	D118 52☉ 005	
		24 V AC, 2 J	D118 52☉ 305	
		230 V AC, 2 J	D118 52☉ 313	

Strobe Beacon Signalling Sounder C €

Type	Description	Specifications	Catalog Number	
			Black Housing	
	VS4 Strobe Beacon Signalling Sounder Not available in yellow 230/240 V AC	Amber	410 401 005	
		Red	410 402 005	
		Clear	410 404 005	
		Blue	410 405 005	
		Green	410 406 005	

LED Flashing Multi-tone Siren C €



Type	Description	Specifications	Catalog Number		
			Red Housing	White Housing	
	CS1 LED Flashing Multi-tone Siren Not available in green or yellow 24 V DC	Amber	C111 621 005	C111 221 005	
		Red	C111 622 005	C111 222 005	

❶ To complete the catalog no., replace the ☉ with one of the following numbers for desired lens color:
 1 = Amber, 2 = Red, 4 = Clear, 5 = Blue, 6 = Green, 7 = Yellow.
 ❷ Special order only. Minimum quantities apply. Contact Sprecher + Schuh for more information.





Mini Horn-Signal Beacons



Type	Description	Specifications	Catalog Number	
	Replace ❷ with lens color		Grey Housing ❶	
	KLL Mini Horn Signal Beacon with cone Steady of Flashing (no bulb) ❷ ❸ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 11❷ 005 710 11❷ 105 710 11❷ 108 710 11❷ 113	
	KLF Mini Horn Strobe Beacon with cone Xenon tube included ❸ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 230/240 V AC, 50 Hz	710 12❷ 005 710 12❷ 113	
	KDL Mini Horn Signal Beacon without cone Steady of Flashing (no bulb) ❷ ❸ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 01❷ 005 710 01❷ 105 710 01❷ 108 710 01❷ 113	
	KDF Mini Horn Strobe Beacon without cone Xenon tube included ❸ 92 dB @ VDC 88 dB @ VAC, 50 Hz	24 V DC 230/240 V AC, 50 Hz	710 02❷ 005 710 02❷ 113	

Mini Horns



Type	Description	Specifications	Catalog Number	
			Grey Housing	
	KLH Mini Horn with cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC 24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 100 004 710 100 005 710 100 010 710 100 013 710 100 105 710 100 108 710 100 113	
	KDH Mini Horn without cone continuous tone 92 dB @ VDC 88 dB @ VAC, 50 Hz	12 V DC 24 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 230 V AC, 50 Hz	710 000 004 710 000 005 710 000 013 710 000 105 710 000 108 710 000 113	

❶ To complete the catalog no., replace the ❷ with one of the following numbers for desired lens color:



1 = Amber, 2 = Red, 7 = Yellow.

❷ Bulb not included. Order separately on page J39.

❸ Other voltages and colors available by special order only. Contact factor for more information.



Signal Horns CE


Type	Description	Specifications	Catalog Number	
		❶	Grey Housing	
	HPT Signal Horn Impact resistant synthetic housing continuous tone (108 dB)	24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 110 V AC, 50 Hz 230 V AC, 50 Hz 120 V AC, 60 Hz 240 V AC, 60 Hz	712 100 005 712 100 010 712 100 013 712 100 105 712 100 108 712 100 110 712 100 113 712 100 211 712 100 213	
	HTG Signal Horn Die-cast aluminum housing continuous tone (108 dB)	24 V DC 110 V DC 220 V DC 24 V AC, 50 Hz 48 V AC, 50 Hz 110 V AC, 50 Hz 230 V AC, 50 Hz 120 V AC, 60 Hz 240 V AC, 60 Hz	713 100 005 713 100 010 713 100 013 713 100 105 713 100 108 713 100 110 713 100 113 713 100 211 713 100 214	

Online Only


❶ Other voltages available by special order only. Contact factory for more information.





Signal Bells **CE**

Type	Description	Specifications	Catalog Number	
			Grey Housing	Red Housing
	Signal Bells BEL Bell tone or quick beat (106 dB)	24 V AC	720 300 105	
		115 V AC	720 300 110	
		230 V AC	720 300 313	
		12 V DC	720 300 004	
		24 V DC	720 300 005	720 400 005

Electronic Multi-tone Sirens **CE**

Type	Description	Specifications	Catalog Number	
			Red Housing	White Housing
	ES1	24 V DC, 32 tones (106 dB)	C110 620 005	C110 220 005
	ES2	110 - 230 V AC, 32 tones (106 dB)	C115 600 113	C115 200 113

Electronic Sounders **CE**





Type	Description	Specifications	Catalog Number	
			Type D (DIP Switch)	Type K (Terminals)
	EHS-D EHS-K Electronic Sounder swiveling speaker (118 dB)	12-24 V AC/DC 230/240 V AC, 40-60 Hz	731 010 405 731 010 313	731 020 405 731 020 313
		EHL-D EHL-K Electronic Sounder short fixed speaker (110 dB)	12-24 V AC/DC 230/240 V AC, 40-60 Hz	730 010 405 730 010 313

J
Non-UL Signaling




M28 Panel Mount Alarms



Type	Description	Specifications	Catalog Number	
			Grey Housing	Black Housing
	ESD Panel Mount Alarm continuous tone (90 dB)	24 V AC/DC 230/240 V AC	810 000 405 810 000 313	810 100 405 810 100 313
	ESP Panel Mount Alarm pulsing tone (90 dB)	24 V AC/DC	811 000 405	811 100 405
	ESZ-S Panel Mount Alarm continuous/pulsing tone with spades (90 dB)	24 V AC/DC 230/240 V AC	809 000 405 809 000 313	809 100 405 809 100 313
	ESZ-K Panel Mount Alarm continuous/pulsing tone with terminal (90 dB)	24 V AC/DC 230/240 V AC	809 010 405 809 010 313	809 110 405 809 110 313
	BU2 Panel Mount Alarm pulsing tone (90 dB) ①	12 V AC/DC 24 V AC/DC		B100 520 404 B100 520 405
	BU3 pulsing tone (90 dB) ①	220 V AC		B100 520 313

BU1 Surface Mount Alarms



	Surface Mount Alarm Electronic Siren pulsing tone (108 dB)	12 V DC 24 V DC		B100 510 004 B100 510 005
---	--	--------------------	--	--

① Adjustable sound pressure.